

4835 Optical Module



Overview

The DS4835 is a low-power, 16-bit microcontroller with a unique peripheral set supporting optical applications that require high-resolution conversion of many analog signals and digital-signal processing (DSP) of those signals, and an external host interface. Integrated circuits and reference designs help you create a smaller and faster optical module design used in high-bandwidth data communication applications. The device integrates various power. OPTICAL MCU, 16BIT, 10MHZ, TQFN-40; Product Range:DS4 Family DS4830 Series Microcontrollers; Archite. Manufacturer: Maxim Integrated Products. Description: Optical Microcontroller 16-Bit MAXQ20 Low-Power Microcontroller. RO4835 material is a high frequency circuit laminate from the Rogers RO4000 series. Unlike standard FR4, it uses a hydrocarbon ceramic-filled system. Elevate your RF and wireless applications with the RO4835IND 2-Layer Industrial Wireless Module Board, now available at PCBsync.



Article Content

RO4835 High-Frequency PCB Laminates for RF, 5G & Automotive

Material Properties ... Applications 5G Infrastructure: High-frequency laminates for base stations and antennas. Automotive Radar: Advanced driver-assistance systems (ADAS). Aerospace

Sartorius Incucyte SX5 G/R Optical Module Set 4832

Sartorius IncuCyte SX5 G/R Optical Module Set PN: 4832 Includes: Optical Module 4817 Phase Lamp 4818 IncuCyte G/R Calibration Kit 4515 Condition: New

RO4835IND 1.2mm 1/2oz Immersion Gold 2-Layer Industrial Wireless Module ...

Elevate your RF and wireless applications with the RO4835IND 2-Layer Industrial Wireless Module Board, now available at PCBsync. Engineered specifically for high-frequency performance and

Used ESKO CDI SPARK 4835 HD flexographic platemaking

Meet US At Ask for machine price Printing Plate Processing Equipment - ESKO - CDI SPARK 4835 HD flexographic platemaking production equipment - Ref.300048864

CDI Spark 4835 Technical specifications

CDI Spark 4835 Technical specifications Based on the FTA and GATF award winning technology of the CDI, the premier and most productive device for flexo imaging, the CDI Spark 4835 specifically

CDI Crystal 4835 XPS

CDI Crystal 4835 XPS Your best match, based on your answers, is the CDI Crystal 4835 XPS flexo imager. Together, we believe you can do great things! The CDI

Oxygen Optode 4835

Oxygen Optode 4835 Since oxygen is involved in most of the biological and chemical processes in aquatic environments, it is the single most important parameter needed to be measured. Oxygen can

Esko 2007 CDI SPARK 4835

• Optics 25 - 2.5m²/hour • Vacuum drum • Suite 10 Grapholas software on PC • Plate thickness: 0,76 mm to 6,35 mm Including: • Upgraded to HD version •

Industrial Gigabit Fiber SFP Optical Transceiver Module

Compatibility in your network is everything, and this industrial SFP Transceiver Module delivers. Use it with any Intellinet SFP equipped network switch or any other Multi Source Agreement (MSA)

Aanderaa 4835 Oxygen Optode

The Aanderaa Oxygen Sensor was the first and only to measure dissolved oxygen for years without drift - now it is one of the fastest! Below you can read more

Optical-Link-Modules_brief_instruction_en_3_Lapp dd

The PROFIBUS Optical Link Module is a normal PROFI-BUS repeater despite its small dimensions. It permits the conversion of electrical PROFIBUS/MPI interfaces to optical PROFIBUS/MPI interfaces.

FOSSIL FFS4835 Datasheet, PDF

FOSMF 111Kb/2P Opticom Splice Modules, Trays, and Holders FOSMH1U 111Kb/2P Opticom Splice Modules, Trays, and Holders FOSMH2U 111Kb/2P Opticom Splice Modules, Trays, and Holders

Optical module

Optical modules can either plug into a front panel socket or an on-board socket. Sometimes the optical module is replaced by an electrical interface module that implements either an active or passive

Optical module design resources | TI

Design requirements Modern optical module designs often require: Reduced power consumption to control and limit module temperature rise. Dynamic and precise control of laser diodes to regulate

Maxim DS4835VGTL | Optical Microcontroller With Tec | Kynix

You can view the stock availability, pricing, and product specifications for the Maxim Optical Microcontroller With Tec DS4835VGTL on Kynix and place an order online.

RO4835 Material Selection Guide for High Frequency PCB

Is RO4835 material the right choice for your high frequency PCB? Learn its Dk, Df, loss behavior, RO4835 LoPro option, and selection tips.

DS4835 Datasheet, PDF

Description: Optical Microcontroller 16-Bit MAXQ20 Low-Power Microcontroller. 11 Results. Datasheet: 1MbKb/29P. Manufacturer: Maxim Integrated Products.

DS4835 Datasheet, PDF

DS4835 Datasheet. Part #: DS4830. Datasheet: 1MbKb/29P. Manufacturer: Maxim Integrated Products. Description: Optical Microcontroller 16-Bit MAXQ20 Low-Power ...

Used Esko Spark CDI 4835 Optics 40 imager for sale

The Esko Spark CDI 4835 Optics 40 is a high-quality digital flexo plate imager designed to meet the demanding requirements of the packaging and label

AEG Vision

Get reviews, hours, directions, coupons and more for AEG Vision. Search for other Opticians on The Real Yellow Pages®.

Optical Module SFP

Multi-mode SFP module with dual fiber, Tx/Rx in the different optical fibers Using same wavelength in different fibers to realize bi-directional

Technical Support: E4832A-ATO 675 Mb/s ParBERT Modules

The Keysight ParBERT 81250 675 Mb/s modules are the ideal solution for testing the parallel side of devices according to Gigabit Ethernet, Digital Video applications and up to OC-192 standards.

CDI Crystal 4835 XPS with PCW

CDI Crystal 4835 XPS with PCW Your best match, based on your answers, is the CDI Crystal 4835 XPS flexo imager, in combination with the Print Control Wizard.

Rogers RO4835 PCB: Properties, Applications & Design Guidelines

RO4835 PCB serves critical roles in 5G infrastructure, particularly in antenna arrays and RF front-end modules. The material's low loss characteristics help maintain signal integrity in sub-6 GHz and

CDI SecuFlex 4835 Technical specifications

CDI SecuFlex 4835 Technical specifications Based on the award winning technology of the Dupont Cyrel™ Digital Imager (CDI), the CDI Spark 4835 SecuFlex delivers digital flexo plates suitable to

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.kilitech.co.za>

Email: info@kilitech.co.za

Phone: +44 20 7183 2649

Address: 1st Floor, The Shard, 32 London Bridge Street, London, SE1 9SG,
United Kingdom

This document is for informational purposes only. Specifications subject to
change without notice.

